

**DURO DYNE CORPORATION**  
130 RT. 110  
FARMINGDALE, N.Y. 11735  
EMERGENCY PHONE NO. 800-424-9300  
INFORMATION PHONE NO. 800-899-3876

<b>H.M.I.S.</b>	
<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>REACTIVITY</b>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<b>B</b>
These ratings should be used only as part of fully implemented H.M.I.S. program.	

# MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION 6/2000

## SECTION I

**TRADE NAME:** DURO DYNE FCA FLEXMASTIC  
**MANUFACTURER CODE I.D.:** FCA

## SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	CAS	OSHA-PEL
ETHYLCYANOACRYLATE "SUPER-GLUE"	None	None

## SECTION III - HEALTH INFORMATION

### EFFECTS OF SHORT TERM EXPOSURE

**INHALATION:** May cause throat irritation, coughing. Causes headaches, irritation to mucus membrane. Remove to fresh air.

**SKIN:** Bonds instantly, do not pull apart. Soak in warm soapy water or apply acetone or polish remover.

**MEDICAL CONDITIONS:** Generally aggravated by exposure.

## SECTION IV - FIRST AID AND EMERGENCY PROCEDURES

**INHALATION:** Remove to fresh air immediately.

**SKIN:** Soak in warm, soapy water or acetone. Do not pull apart, will separate by itself.

## SECTION V - PHYSICAL DATA

**BOILING RANGE:** 149°F.

**VAPOR DENSITY:** (mm/Hg.) 0.17 @ 20°C.

**EVAPORATION RATE:** None

**SOLUBILITY IN WATER:** Insoluble

**APPEARANCE AND ODOR:** Clear, acrid odor

**SPECIFIC GRAVITY (H<sub>2</sub>O=1):** 1.046

## SECTION VI - FIRE AND EXPLOSION DATA

**FLASHPOINT:** >200°F

**EXTINGUISHING MEDIA:**

Foam or carbonic acid

**UNUSUAL FIRE AND EXPLOSION HAZARDS:**

None

**SPECIAL FIRE FIGHTING PROCEDURES:**

Firefighters should wear self-contained breathing apparatus.

## SECTION VII - REACTIVITY DATA

**STABILITY:** Stable.

**CONDITIONS TO AVOID:** Storage in contact with or near heat, moisture, sunlight.

**INCOMPATIBILITY (MATERIALS TO AVOID):** Water, bases alcohol.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Burning, including when heated by welding or cutting, will produce smoke, carbon monoxide and carbon dioxide.

**HAZARDOUS POLYMERIZATION:** Will not occur.

## SECTION VIII - PERSONAL PROTECTION INFORMATION

**VENTILATION-LOCAL EXHAUST:** OK

**SKIN:** Use protective gloves

**EYES:** Use protective goggles

## SECTION IX - SAFE HANDLING AND USE

**IF MATERIAL IS SPILLED OR RELEASED:** Flush with generous amounts of water. Allow to harden and break up and dispose of normally.

**DISPOSAL METHODS:** Dispose in accordance with current Local, State and Federal Regulations.

**STORAGE AND HANDLING:** Material should be handled and stored in a cool, dry area. Containers should be kept tightly closed. Avoid storage in sunlight. For best results material should be refrigerated.