

DURO DYNE CORPORATION
130 RT. 110
FARMINGDALE, N.Y. 11735
EMERGENCY PHONE NO. 800-424-9300
INFORMATION PHONE NO. 800-899-3876

H.M.I.S.	
HEALTH	1
FLAMMABILITY	1
REACTIVITY	1
PERSONAL PROTECTION	B

These ratings should be used only as part of fully implemented H.M.I.S. program.

MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION 6/2000

SECTION I

TRADE NAME: DURO DYNE HEAVY EXCELON FABRIC
MANUFACTURER CODE I.D.: DBX

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	OSHA/PEL	ACGIH/TLV
ANTIMONY (V) OXIDE	0.5 mg/m ³	(as Sb)
BARIUM/CADMIUM STABILIZER	0.2 mg/m ³ 0.5 mg/m ³	(as Cd) (as Ba)
10,10' OXYBISPHENOXARSINE	0.5 mg/m ³	(as As)

SECTION III - FIRST AID AND EMERGENCY PROCEDURES

SWALLOWING: Toxicity due to ingestion of small amounts believed very low.

INHALATION: Not normally hazardous unless material at elevated temperatures. Remove to fresh air.

EYES: Irrigate with water for 15 minutes. Consult medical personnel.

SKIN: Not normally hazardous. Consult physician in case of skin irritation.

SECTION IV - PHYSICAL DATA

COLOR: Black	BOILING POINT: N.A.	REACTIVITY IN WATER: Unreactive
ODOR: Characteristic vinyl odor	VAPOR PRESSURE (mm Hg): N.A.	MELTING POINT: >160°F
PHYSICAL STATE: Solid	SOLUBILITY IN WATER: Insoluble	

SECTION V - FIRE AND EXPLOSION DATA

FLASHPOINT: >300°C

AUTOIGNITION TEMPERATURE: >400°C

EXTINGUISHING MEDIA: CO₂, water spray, dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should wear self-contained breathing apparatus.

SECTION VI - ENVIRONMENTAL INFORMATION

STEPS TO BE TAKEN IN HANDLING AND STORAGE:

Avoid high temperatures.

SPILL INFORMATION:

None known.

WASTE DISPOSAL:

Dispose of in accordance with Federal, State, and Local Health and Pollution Laws and Regulations.

SECTION VII - PERSONAL PROTECTION INFORMATION

EYES: Standard safety glasses.

RESPIRATORY: Not required unless product submitted to elevated temperatures.

VENTILATION: Do not exceed TLVs.