

**DURO DYNE CORPORATION**  
130 RT. 110  
FARMINGDALE, N.Y. 11735  
EMERGENCY PHONE NO. 800-424-9300  
INFORMATION PHONE NO. 800-899-3876

<b>H.M.I.S.</b>	
<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>2</b>
<b>REACTIVITY</b>	<b>0</b>
<b>PERSONAL PROTECTION</b>	
These ratings should be used only as part of fully implemented H.M.I.S. program.	

# MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION 6/2000

## SECTION I

**TRADE NAME:** DURO DYNE PBA - PERFORATED BASE ADHESIVE  
**MANUFACTURER CODE I.D.:** PBA

## SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

INGREDIENT	CAS #	PERCENT	OSHA PEL PPM	ACGIH TLV	OSHA, ACGIH STEL PPM	SARA	VP mmHg @20°C
XYLENE*	1330-20-7	1-5	100	100	150	x	6
METHYLCYCLOPENTANE	96-37-7	5-10					
n-HEXANE	110-54-3	30-50	50	50	1000	x	120
TOLUENE*	108-88-3	5-10	100	50	150		24
VM&P NAPHTHA	8032-32-4	10-30					

**\* SKIN ABSORPTION MAY POTENTIALLY CONTRIBUTE TO THE OVERALL EXPOSURE TO THIS MATERIAL. APPROPRIATE MEASURES SHOULD BE TAKEN TO PREVENT ABSORPTION SO THAT THE TLV IS NOT INVALIDATED.**

## SECTION III - HEALTH INFORMATION

**EYES:** Contact with the product or high vapor will cause irritation.

**SKIN:** Liquid contact will dry and defat skin. Prolonged or repeated contact may cause irritation.

**INHALATION:** Overexposure to vapors in poorly ventilated areas will cause irritation of the nose, throat and respiratory tract and may cause dizziness, headaches, nausea or unconsciousness.

**INGESTION:** Harmful if swallowed.

**CHRONIC:** n-Hexane has been demonstrated to cause peripheral nerve damage in overexposed workers. Symptoms include loss of feeling and weakness in the hands and feet and loss of manual dexterity.

Overexposure to Toluene may cause female and male reproductive disorders, based on tests with laboratory animals.

Current exposure guidelines are expected to protect from these effects. Overexposure to Xylene may cause female and male reproductive disorders, based on tests with laboratory animals.

Long-term overexposure to solvents may cause liver and kidney damage. Some solvents may cause damage to the nervous system.

**REGULATED CARCINOGEN STATUS:** Unless noted below, this product does not contain regulated levels of NTP, IARC, ACGIH or OSHA listed carcinogens.

## SECTION IV - FIRST AID AND EMERGENCY MEASURES

**EYES:** Flush immediately with large amounts of water for at least 15 minutes. Call a physician.

**SKIN:** Wash affected area with soap and water. Launder contaminated clothing before reuse.

**INHALATION:** Remove from exposure. Restore breathing if necessary. Keep warm and quiet. Call a physician.

**INGESTION:** If person can swallow, give one glass of water or milk. Do not induce vomiting. Get immediate medical attention. Never give anything by mouth to an unconscious person.

## SECTION V - PHYSICAL DATA

**PHYSICAL STATE:** Liquid

**COLOR:** Gray

**ODOR:** Solvent

**ODOR THRESHOLD:** N.E.

**WEIGHT PER GALLON:** 7.2 Lbs.

**SPECIFIC GRAVITY:** .86

**% SOLIDS BY WEIGHT:** 46.3

**VOC:** N.E.

VOC, less water: 463.76g VOC/liter of material, less water and exempt solvents

**PH:** N.E.

**BOILING RANGE:** Greater than 156° F (69°C)

**FREEZING/MELTING POINT:** N.E.

**VAPOR PRESSURE:** N.E.

**VAPOR DENSITY:** N.E.

**EVAPORATION RATE:** N.E.

**WATER/OIL PARTITION COEFFICIENT:** N.E.

## SECTION VI - FIRE AND EXPLOSION DATA

**FLASH POINT METHOD:** 20 degrees F Pinsky-Martens, -7 degrees C

**U.E.L./ L.E.L.:** N.E.

**AUTOIGNITION:** N.E.

**EXTINGUISHERS:** Use water spray, foam, dry chemical or carbon dioxide.

**SPECIAL FIRE FIGHTING PROCEDURES:** Persons exposed to products of combustion should wear contained breathing apparatus and full protective equipment.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** There is the possibility of pressure buildup in closed containers when heated. Water spray may be used to cool the containers. Solvent vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames and ignition sources at locations distant from the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

## SECTION VII - REACTIVITY DATA

**STABILITY:** Stable

**INCOMPATIBILITY:** N.E.

**HAZARDOUS DECOMPOSITION:** N.E.

**HAZARDOUS POLYMERIZATION:** Will not occur

## SECTION VIII - ENVIRONMENTAL INFORMATION

This product meets the definition of hazardous waste under the U.S. EPA Hazardous Waste Regulations 40 CFR 261. It is ignitable waste class D001. Disposal via incineration is recommended. Consult your state, local or provincial authorities for more restrictive requirements.

## SECTION IX - PERSONAL PROTECTION INFORMATION

**EYES:** Wear safety glasses to reduce the potential for eye contact; chemical safety goggles are appropriate if splashing or dusting is likely. Have eye washes available where eye contact can occur.

**SKIN:** Prevent contact by using rubber gloves and appropriate protective clothing. Launder contaminated clothing before reuse.

**INHALATION:** Use NIOSH approved supplied air respirator if conditions warrant.

**VENTILATION:** Local exhaust ventilation preferred. Provide ventilation to control contaminant levels below airborne exposure limits.

## SECTION X - SPECIAL PRECAUTIONS

### HANDLING AND STORAGE

Keep away from heat.

Avoid breathing vapors.

Use only with adequate ventilation.

Avoid contact with eyes, skin and clothing.

Wash thoroughly after handling.

Keep container closed.

Emptied container retains vapor and product residue.

Observe all labeled precautions until container is cleaned.

**DO NOT CUT OR WELD ON OR NEAR THIS CONTAINER**

## SECTION XI - OTHER INFORMATION

**THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED TO BE ACCURATE. WHILE THE INFORMATION IS BELIEVED TO BE RELIABLE, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THIS DATA OR THE RESULTS TO BE OBTAINED FROM THE USER THEREOF. SINCE THE USE OF THIS INFORMATION AND THE CONDITIONS AND USE OF THIS PRODUCT ARE CONTROLLED BY THE USER, IT IS THE USER'S OBLIGATION TO DETERMINE THE CONDITIONS OF SAFE USE OF THE PRODUCT.**