

DURO DYNE CORPORATION
130 RT. 110
FARMINGDALE, N.Y. 11735
EMERGENCY PHONE NO. 800-424-9300
INFORMATION PHONE NO. 800-899-3876

| | |
|--|----------|
| H.M.I.S. | |
| HEALTH | 1 |
| FLAMMABILITY | 2 |
| REACTIVITY | 0 |
| PERSONAL PROTECTION | B |
| These ratings should be used only as part of fully implemented H.M.I.S. program. | |

MATERIAL SAFETY DATA SHEET

DATE OF PREPARATION 6/2000

SECTION I

TRADE NAME: DURO DYNE SILICONIZED ACRYLIC DUCT SEALER
MANUFACTURER CODE I.D.: SAS

SECTION II - COMPOSITION/INFORMATION ON INGREDIENTS

| INGREDIENT | CAS # | PERCENT | OSHA PEL PPM | ACGIH TLV | OSHA, ACGIH STEL PPM | SARA | VP mmHg @20°C |
|-----------------------------|------------|---------|-----------------|-----------|-------------------------|------|------------------|
| MINERAL SPIRITS | 64742-88-7 | 1.07 | 500 | 100 | | | |
| CALCIUM CARBONATE** | 1317-65-3 | >60.0 | 15 | 10 | | | |
| ETHYLENE GLYCOL*** | | .90 | 50 | 50 | | | |
| BENZOATE ESTER | 27138-31-4 | >6 | | | | | |
| BIS (TRIBUTYL TIN) OXIDE*** | 56-35-9 | <.05 | | | | | |
| OCTYLPHENOL ETHOXYLATE | 9036-19-5 | | | | | | |

** Inhalation of particulates unlikely due to product's physical state.

*** Combustible material. Store in a closed container in a cool area. This product contains bis (tributyltin) oxide and the minimum value of ethylene glycol, ingredients listed in Section 313 of SARA Title III and 40 CFR 372.65.

SECTION III - FIRST AID AND EMERGENCY MEASURES

EFFECTS OF OVEREXPOSURE: Inhalation of dust generated from dried product may cause respiratory irritation. High vapor concentrations may produce headache, dizziness and nausea. Prolonged or repeated contact may cause mild skin and eye irritation.

EYES: Flush immediately with large amounts of water while holding the eyelids open. Get medical attention if irritation persists.

SKIN: Wipe material from skin with cloth or paper towel, then wash exposed area with soap and water. Get medical help if irritation persists.

INHALATION: Remove subject to fresh air and treat symptomatically.

INGESTION: Contact local poison control center or physician IMMEDIATELY!

SECTION IV - PROTECTION INFORMATION

EYES: Wear safety glasses.

SKIN: In situations of extended skin contact, neoprene or other chemical resistant gloves are recommended.

INHALATION: Not normally required. If TLV is exceeded, or for symptoms of overexposure, wear a NIOSH approved respirator for organic vapors.

VENTILATION: Provide adequate general dilution ventilation.

SECTION V - PHYSICAL DATA

PHYSICAL STATE: Paste
COLOR: White
ODOR: Mild acrylic
VAPOR PRESSURE: N.E.
VAPOR DENSITY: >1

PH: 7.5 - 8.0
SOLUBILITY IN WATER: Appreciable
FREEZING/MELTING POINT: N.E.
EVAPORATION RATE: >1 (BuAc=1)
SPECIFIC GRAVITY: 1.5 - 1.75

SECTION VI - FIRE AND EXPLOSION DATA

FLASH POINT: 150°
U.E.L./ L.E.L.: N.E.
EXTINGUISHERS: Carbon dioxide, dry chemical or foam
SPECIAL FIRE FIGHTING PROCEDURES: Use water spray or fog to cool fire-exposed containers.

SECTION VII - REACTIVITY DATA

STABILITY: Stable. Avoid extreme heat, open flame.
INCOMPATIBLE MATERIALS: Strong oxidizers.
HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide

SECTION VIII - HANDLING PROCEDURES

Clean up with absorbent material. Dispose of in accordance with Local, State and Federal Regulations.